



# PC-A370D



**HD  
ready**

Key Communication Media

|                                |  |
|--------------------------------|--|
| <b>Panel</b>                   | 37" (940.3mm ) TFT-LCD                         |
| <b>Resolution</b>              | WXGA 1366 x 768 (1920x1080)                    |
| <b>Response Time</b>           | 8ms  |
| <b>Aspect Ratio</b>            | 16:9   |
| <b>Colors</b>                  | 16.2 M   |
| <b>Horizontal Freq.</b>        | 48.4~60KHz                                     |
| <b>Vertical Freq.</b>          | 60~75Hz  |
| <b>Contrast</b>                | 800:1  |
| <b>Brightness</b>              | 500 cd/m <sup>2</sup>                          |
| <b>Viewing Angle</b>           | >176°/176° (U,D/R,L)                           |
| <b>System</b>                  | NTSC, PAL, SECAM                               |
| <b>DTV</b>                     | 480p, 576p, 720p, 1080i                        |
| <b>Progressive Scan</b>        | Yes  |
| <b>Inputs</b>                  | HD15, C-Video, S-Video, 2xScart, Component, TV |
| <b>DPMS</b>                    | Standard VESA DPMS                             |
| <b>Power</b>                   | AC 110-240V, 50/60 Hz                          |
| <b>Consumption</b>             | Max 253W                                       |
| <b>Dimensions</b>              | 1085mm(W) X 635mm(H) X 304mm(D)                |
| <b>Dimension without stand</b> | 1085mm(W) X 564mm(H) X 117mm(D)                |
| <b>Weight</b>                  | 27 Kg  |

### Integrated PC

|                    |   |
|--------------------|---|
| <b>Motherboard</b> | Commel 915G Mini-itx  |
| <b>Processor</b>   | Intel® Centrino 1.7 GHz, 2MBK, 533 MHz, Sonoma Tech.        |
| <b>Chipset</b>     | Intel® 915GM (Northbridge) and ICH6-M (Southbridge)         |
| <b>Graphic</b>     | Intel® 915GM GMCH up to 128Mb Shared                        |
| <b>Hard Disk</b>   | Seagate 160Gb SATA II, 7200 Rpm, 8Mb                        |
| <b>BIOS</b>        | Phoenix -Award v6.00PG 4Mb PnP flash BIOS                   |
| <b>RAM</b>         | Kingstone DDR2 512Mb 533MHz non ECC                         |
| <b>USB</b>         | 2 x 2.0 Hi-Speed ports with 480Mbps of transfer rate        |
| <b>LAN</b>         | Marvell E8053 Gigabit Ethernet Controller 10/100/1000Base-T |
| <b>PS/2</b>        | KB/MS ports   |

### Operating System

|           |                                     |
|-----------|-------------------------------------|
| <b>OS</b> | Windows® Vista, XP Professional OEM |
|-----------|-------------------------------------|

### Option

|                    |                      |
|--------------------|----------------------|
| <b>Speakers</b>    | 10W x 2 stereo       |
| <b>Table Stand</b> | Silver               |
| <b>Wall Mount</b>  | With or without Tilt |
| <b>RAM</b>         | up to 2Gb            |
| <b>Hard Disk</b>   | from 40 up to 750Gb  |



**K.C.M. S.r.l.**

Via Corridori n. 52 – 20037 Paderno Dugnano (MI) – Tel: ++39 0299043377 – Fax: ++39 0299043390  
www.kcm.it E-Mail: info@kcm.it